



cement with style

NEUTRAL BINDER

Mixx is a thin-film, cement-based trowel coating that can adhere to almost any surface with minimal preparation.

Neutral Binder can be used to thin your trowel mixture, allowing it to be used for other exciting applications such as a matt paint finish or as a dipping medium.

Technical Data

| | |
|---------------------|---|
| Product | Mixx Neutral binder |
| Type | Co-polymer Styrene Acrylic |
| Components | To be used to thin your Mixx Mixture |
| Packaging | 1000 g |
| Mix Ratio | Dependant on application |
| | To convert Mixture to paint - Add 1 cup |
| | To convert Mixture to dip - Add 2 cups |
| Ambient temperature | 25 ° Celcuis |

Directions

- Shake **Neutral Binder** well before use.
- For a **Paintable Paint**: add **Neutral Binder** to your ready mixed coating at a recommended ratio of 100g (1 Mixx Cup) or simply thin as desired.
- For a **Dipping Medium**: add **Neutral Binder** to your ready mixed trowel coating, at a recommended ratio of 200g (2 Mixx Cups) or simply thin as desired.
- Remix your mixture into a smooth, lump-free thinner mix.
- Should you require a more liquid consistency for your project, simply add more **Neutral Binder**.
- **Neutral Binder** can also be added to your coating to reconstitute your mixture after you have saved it for up to three dyas.

Cleaning

Clean all tools, brushes and bowls immediately after use with clean water.

Storage

Neutral Binder can be stored, sealed, in a cool dry place for up to 12 months.

If the product comes into contact with eyes, rinse well with water and if irritation persists, seek medical advice.

For more directions on the various uses of our products, speak to your stockist or visit our social media pages.

Mixx is manufactured to the highest quality standards.

Produced and packaged in Tzaneen, South Africa.

www.mixxcement.co.za