



cement with style

**PRIMER**

Mixx is a thin-film, cement-based trowel coating that can adhere to almost any surface with minimal preparation.

**Primer** is a water-based coating, that will provide excellent adhesion onto difficult substrates like ceramic tiles and melamine.

### Technical Data

Product	Mixx Primer
Type	Latex
Packaging	1000 g
Coverage	Dependant on surface and porosity
	Smooth surface = 10m <sup>2</sup>
	Rough surface = 6m <sup>2</sup>
Touch dry	4 hours
Overcoat	6 hours
Full cure	48 hours
Ambient temperature	25 ° Celcius

### Directions & Application

- Shake the **Primer** and pour contents into a paint tray or suitable container.
- Depending on surface, apply with either a sponge applicator, a sponge roller, a short hair roller or a blondie brush.
- Ensure surface to be primed, is clean.
- Apply the **Primer** in a thin, even coat.
- Allow to dry for 4 hours.

### Cleaning

Clean all tools, brushes and rollers immediately after use, with clean water

### Storage

**Primer** can be stored, sealed in a cool dry area for up to 12 months.

If the product comes into contact with eyes, rinse well with water and if irritation persists, seek medical advice.

For more directions on the various uses of our products, speak to your stockist or visit our social media pages.

Mixx is manufactured to the highest quality standards.

Produced and packaged in Tzaneen, South Africa.

[www.mixxcement.co.za](http://www.mixxcement.co.za)