



cement with style

SERIOUS SEAL

Mixx is a thin-film, cement-based trowel coating, that once applied, needs to be sealed to maintain, enhance and protect your finish. If not sealed, the colour will change when exposed to the elements.

Serious Seal is recommended for use in low moisture areas like splashbacks or scratch resistance is needed.

Technical Data

Product	Mixx Serious Seal
Type	Cross linking Acrylic
Packaging	500 g
Coverage	Dependant on surface and porosity
	Smooth surface = 10m ²
	Rough surface = 6m ²
Touch dry	4 hours
Overcoat	6 hours
Full cure	72 hours
Ambient temperature	25 ° Celsius

Directions & Application

- **Serious Seal** is a single-pack system. Simply shake the **Serious Seal**. Pour contents into a paint tray or suitable container, and your sealer is ready for use.
- Dependant on what surface, apply with either a sponge applicator, a sponge roller, a short hair roller or a blondie brush.
- Apply **Serious Seal** in a thin even coat, ensuring you overlap and cover the entire area. A second coat can be applied after 4 hours when dry. Full cure will be reached within 24 hours.

Serious Seal is extremely difficult to remove off surfaces once it hardens, so ensure you wipe any drip marks from surfaces.

Cleaning

Clean all tools, brushes and rollers immediately after use, with clean water.

Storage

Sealer can be stored, sealed in a clean dry area for up to 12 months.

If the product comes into contact with eyes, rinse well with water and if irritation persists, seek medical advice.

For more directions on the various uses of our products, speak to your stockist or visit our social media pages.

Mixx is manufactured to the highest quality standards.

Produced and packaged in Tzaneen, South Africa.

www.mixxcement.co.za