



cement with style

SILLY SEAL

Mixx is a thin-film, cement-based trowel coating, that once applied, needs to be sealed to maintain, enhance and protect your finish. If not sealed, the colour will change when exposed to the elements.

Silly Seal is an acrylic based sealer used to protect items that are not exposed to extreme wear and tear or water.

Technical Data

Product	Mixx Silly seal
Type	Acrylic
Packaging	500 g
Coverage	Dependant on surface and porosity
	Smooth surface = 12m ²
	Rough surface = 8m ²
Touch dry	2-3 hours
Overcoat	6 hours
Full cure	48 hours
Ambient temperature	25 ° Celsius

Directions & Application

- Shake the **Silly Seal**, and pour contents into a paint tray or suitable container.
- Dependant on what surface, apply with either a sponge applicator, a sponge roller, a short hair roller or a blonde brush.
- Apply **Silly Seal** in a thin even coat, ensuring you overlap and cover the entire area. A second coat can be applied after 4 hours. Full cure will be reached within 24 hours.
- Ensure you cover the entire area and use a lint-free cloth to wipe off any excess **Silly Seal**, to avoid spoiling your finish.

Silly Seal is extremely difficult to remove off surfaces once it hardens, so ensure you wipe any drip marks from surfaces.

Cleaning

Clean all tools, brushes and rollers immediately after use, with clean water.

Storage

Sealer can be stored, sealed in a clean dry area for up to 12 months.

If the product comes into contact with eyes, rinse well with water and if irritation persists, seek medical advice.

For more directions on the various uses of our products, speak to your stockist or visit our social media pages.

Mixx is manufactured to the highest quality standards.

Produced and packaged in Tzaneen, South Africa.

www.mixxcement.co.za