cement with style

COLOUR BINDER

Mixx is a thin-film, cement-based trowel coating that can adhere to almost any surface with minimal preparation. **Mixx Colour Binder** is used to bind the Mixx Cement Powder into a thin film, trowel coat, that is ready for application.

Technical Data

Product	Mixx Colour Binder
Type	Co-polymer Styrene Acrylic
Components	To be used with Mixx Cement Powder
Packaging	538 g
Mixx Ratio	1 bottle colour binder + 1 Pack Mixx Cement Powder
Protective Gear	Gloves if needed
Colours	36
Coverage	Dependant on surface and or technique:
	Trowel - smooth surface = 7 - 9m²
	Paint - smooth surface = 4 - 6m²
Dry film thickness	0.7mm per coat total of 1,4mm 2 coats
Pot life	Weather dependant - Aproximately 4 hours
Touch dry	1-2 hours
Walk on	6 hours
Overcoat	6 - 8 hours
Full cure	48 hours
Ambient temperature	25 ° Celcuis

Directions and Application

Your mixture requires both **Mixx Colour Binder** and Mixx Cement Powder. Shake the **Mixx Colour Binder** well and pour all the contents into a mixing bowl. Add the Cement Powder slowly while whisking until a smooth, lump-free consistency is achieved. Your mixture is ready for application as a thin-film, trowel coat.

Mixx can be applied as a trowel coat using a Mixx trowel in windscreen wiper movements, maintaining a thin-film of approximately 0.7mm thick per coat. Your final coat thickness for two towel coats and sealer is approximately 1,4 – 1,5mm thick.

For best application methods we suggest you contact your nearest stockist to do a Mixx cement workshop.

Mixx is manufactured to the highest quality standards.
Produced and packaged in Tzaneen, South Africa.

www.mixxcement.co.za

Cleaning
Clean all tools, brushes and bowls immediately after use, with clean water.

Storage
Colour Binder can be stored unmixed in a cool dry area for up to 12 months. The mixed product can be stored for up to 3 days in an airtight container. Reconstitute mixture with neutral binder if necessary.

Sealer
Once you have applied your Mixx coating, it is recommended to seal the surface to enhance and protect your finished product. For more information on the best Mixx Sealer to use for your project, ask your stockist or visit our website.

The product can cause irritation to eyes. If the product comes into contact with eyes, rinse well with water and if irritation persists, seek medical advice.

For more directions on the various uses of our products, speak to your stockist or visit our social media pages.