cement with style

SILLY SEAL DATA SHEET

DESIGNER CEMENT COATINGS

www.mixxcement.co.za

Silly Seal is an acrylic based cement sealer suited to coat and protect the Mixx cement coating range. Silly Seal is UV Stable and is suitable to highlight and protect your cement finish.

TECHNICAL DATA

Product	Silly Seal
Type	Styrene Acrylic
Application tools	Blondie Brush - Cut pile roller and mutton cloth
Packaging	2L
Finish	Matt
Coverage	8 - 10m^2 /L
Surface Dry	4 hours
Overcoat	4 hours
Full cure	72 hours
Ambient Temperature	6 - 25°C
UV Resistance	Stable and non-yellowing
Storage	In a cool dry place

SUITABLE SURFACES

Mixx Silly Seal is designed as a protective coating for our designer cement coatings. If there is a prevalence of water it is advisable to apply two coats of Silly Seal followed by a coat of Mixx Supreme Seal. Ensure the surface that is being sealed is fully cured prior to applying your sealer.

PRODUCT FEATURES

Easy to apply
UV stable (Non-yellowing)
Washable

SURFACE PREPARATIONS

Ensure the surface is clean, dust free and fully cured prior to applying Silly Seal.

Mixx Cement with Style Head Office
Amorentia Estate, Grootbosch Road, Politsi, Tzaneen
(+27)81 329 2773 | orders@mixxcement.co.za

APPLICATION

Prior to application ensure that the surface is dust free, and fully cured. Ensure that all edges are neatly taped with masking tape. Using a 75mm blondie brush cut the edges and roll sealer with a cut pile roller ensuring an even film thickness. Wipe off any excess sealer with a lint free cloth. Do not cut edges ahead, cut and roll simultaneously. Silly Seal is a two-coat application and a second coat can be applied after 4 hours.

MAINTENANCE AND CARE

Surfaces treated with Colour Stay Sealer can be washed using either a cloth or a soft brush with warm water or some light eco-friendly soapy water.

Disclaimer Advice

Mixx Cement with Style provides all information based on many years of experience in the field of cement coating application and manufacture. The information is given in good faith but no guarantee of any performance characteristic is given or implied. Mixx Cement with Style cannot be held liable for consequential damage of whatsoever nature that may rise from the use of the Mixx product by third parties.

The use of information provided is done at your own risk and Mixx Cement with Style, its suppliers, agents or associates accept no liability for any damages arising out of the use or inability to use the information provided.

Mixx Cement with Style Head Office
Amorentia Estate, Grootbosch Road, Politsi, Tzaneen
(+27)81 329 2773 | orders@mixxcement.co.za